

New Jersey Department of Health and Senior Services

HAZARDOUS SUBSTANCE FACT SHEET

Common Name: tert-BUTYL CHROMATE

CAS Number: 1189-85-1 DOT Number: None

HAZARD SUMMARY

- tert-Butyl Chromate can affect you when breathed in and may be absorbed through your skin.
- Contact can cause severe eye and skin irritation and burns with possible damage to the eyes.
- Breathing tert-Butyl Chromate can irritate the nose and throat causing coughing and wheezing.
- Exposure to tert-Butyl Chromate can cause headache, nausea, vomiting and diarrhea.
- Breathing tert-Butyl Chromate can cause a hole in the "bone" dividing the inner nose (septum), sometimes with discharge, bleeding and/or formation of a crust.
- tert-Butyl Chromate may cause a skin allergy. If allergy develops, very low future exposure can cause itching and a skin rash.
- tert-Butyl Chromate is a FLAMMABLE MIXTURE and a FIRE HAZARD.

IDENTIFICATION

tert-Butyl Chromate is a clear, colorless liquid. It is used in specialty chemical reactions as an organic source of Chromium, in making catalysts, and as a curing agent for *Urethane* foams.

REASON FOR CITATION

- tert-Butvl Chromate is on the Hazardous Substance List because it is regulated by OSHA and cited by NIOSH, ACGIH, DEP, and EPA.
- * Definitions are provided on page 5.

HOW TO DETERMINE IF YOU ARE BEING **EXPOSED**

The New Jersey Right to Know Act requires most employers to label chemicals in the workplace and requires public employers to provide their employees with information and training concerning chemical hazards and controls. The federal OSHA Hazard Communication Standard, 1910.1200, requires private employers to provide similar training and information to their employees.

Exposure to hazardous substances should be routinely evaluated. This may include collecting personal and area air samples. You can obtain copies of sampling results from your employer. You have a legal right to this information under OSHA 1910.20.

RTK Substance number: 1788

Date: November 1986 Revision: September 1998

If you think you are experiencing any work-related health problems, see a doctor trained to recognize occupational diseases. Take this Fact Sheet with you.

WORKPLACE EXPOSURE LIMITS

The legal airborne permissible exposure limit is OSHA: **0.1 mg/m³** (as *Chromic Acid*), not to be exceeded

at any time.

NIOSH: The recommended airborne exposure limit is

0.001 mg/m³ (as hexavalent Chromium) averaged

over a 10-hour workshift.

The recommended airborne exposure limit is ACGIH:

0.1 mg/m³, which should not be exceeded at any

time.

The above exposure limits are for air levels only. When skin contact also occurs, you may be overexposed, even though air levels are less than the limits listed above.

WAYS OF REDUCING EXPOSURE

- * Where possible, enclose operations and use local exhaust ventilation at the site of chemical release. If local exhaust ventilation or enclosure is not used, respirators should be worn.
- Wear protective work clothing.
- Wash thoroughly immediately after exposure to tert-Butyl **Chromate** and at the end of the workshift.
- Post hazard and warning information in the work area. In addition, as part of an ongoing education and training effort, communicate all information on the health and safety hazards of tert-Butyl Chromate to potentially exposed workers.

This Fact Sheet is a summary source of information of <u>all potential</u> and most severe health hazards that may result from exposure. Duration of exposure, concentration of the substance and other factors will affect your susceptibility to any of the potential effects described below.

HEALTH HAZARD INFORMATION

Acute Health Effects

The following acute (short-term) health effects may occur immediately or shortly after exposure to **tert-Butyl Chromate**:

- * Contact can cause severe eye and skin irritation and burns with possible damage to the eyes.
- * Breathing **tert-Butyl Chromate** can irritate the nose and throat causing coughing and wheezing.
- * Exposure to **tert-Butyl Chromate** can cause headache, nausea, vomiting and diarrhea.

Chronic Health Effects

The following chronic (long-term) health effects can occur at some time after exposure to **tert-Butyl Chromate** and can last for months or years:

Cancer Hazard

* While **tert-Butyl Chromate** has not been identified as a carcinogen, certain kinds of *Chromium compounds*, known as *hexavalent Chromium* or *Chromium VI compounds*, have been determined to be human carcinogens. **tert-Butyl Chromate** is such a compound and should be handled with extreme caution.

Reproductive Hazard

* According to the information presently available to the New Jersey Department of Health and Senior Services, **tert-Butyl Chromate** has not been tested for its ability to affect reproduction.

Other Long-Term Effects

- * Breathing **tert-Butyl Chromate** can cause a hole in the "bone" dividing the inner nose (septum), sometimes with discharge, bleeding and/or formation of a crust.
- * tert-Butyl Chromate may cause a skin allergy. If allergy develops, very low future exposure can cause itching and a skin rash.
- * tert-Butyl Chromate may cause an asthma-like allergy. Future exposure can cause asthma attacks with shortness of breath, wheezing, cough, and/or chest tightness.
- * Prolonged skin contact can cause burns, blisters and deep ulcers.

MEDICAL

Medical Testing

For those with frequent or potentially high exposure (half the TLV or greater), the following are recommended before beginning work and at regular times after that:

* Exam of the skin and nose.

If symptoms develop or overexposure is suspected, the following may be useful:

- * Evaluation by a qualified allergist, including careful exposure history and special testing, may help diagnose skin allergy.
- * Lung function tests. These may be normal if the person is not having an attack at the time of the test.
- * Check your skin daily for little burns or blisters, the first sign of "chrome ulcers". If not treated early, these can last for years after exposure.

Any evaluation should include a careful history of past and present symptoms with an exam. Medical tests that look for damage already done are <u>not</u> a substitute for controlling exposure.

Request copies of your medical testing. You have a legal right to this information under OSHA 1910.20.

Conditions Made Worse By Exposure

- * Persons with any cuts or scratches on their hands or other skin surfaces are at increased risk of developing ulcers on skin contact. Good work practices, protective clothing or removal from exposure is essential to prevent serious ulcers.
- Persons with a history of skin allergy to *Chromium compounds* may be more likely to develop a skin allergy to **tert-Butyl Chromate**.

WORKPLACE CONTROLS AND PRACTICES

Unless a less toxic chemical can be substituted for a hazardous substance, **ENGINEERING CONTROLS** are the most effective way of reducing exposure. The best protection is to enclose operations and/or provide local exhaust ventilation at the site of chemical release. Isolating operations can also reduce exposure. Using respirators or protective equipment is less effective than the controls mentioned above, but is sometimes necessary.

In evaluating the controls present in your workplace, consider: (1) how hazardous the substance is, (2) how much of the substance is released into the workplace and (3) whether harmful skin or eye contact could occur. Special controls should be in place for highly toxic chemicals or when significant skin, eye, or breathing exposures are possible.

In addition, the following controls are recommended:

- * Where possible, automatically pump liquid **tert-Butyl Chromate** from drums or other storage containers to process containers.
- * Before entering a confined space where **tert-Butyl Chromate** may be present, check to make sure that an explosive concentration does not exist.

Good **WORK PRACTICES** can help to reduce hazardous exposures. The following work practices are recommended:

- * Workers whose clothing has been contaminated by **tert-Butyl Chromate** should change into clean clothing promptly.
- * Do not take contaminated work clothes home. Family members could be exposed.
- * Contaminated work clothes should be laundered by individuals who have been informed of the hazards of exposure to **tert-Butyl Chromate**.
- * Eye wash fountains should be provided in the immediate work area for emergency use.
- * If there is the possibility of skin exposure, emergency shower facilities should be provided.
- * On skin contact with **tert-Butyl Chromate**, immediately wash or shower to remove the chemical. At the end of the workshift, wash any areas of the body that may have contacted **tert-Butyl Chromate**, whether or not known skin contact has occurred.
- * Do not eat, smoke, or drink where **tert-Butyl Chromate** is handled, processed, or stored, since the chemical can be swallowed. Wash hands carefully before eating or smoking.

PERSONAL PROTECTIVE EQUIPMENT

WORKPLACE CONTROLS ARE BETTER THAN PERSONAL PROTECTIVE EQUIPMENT. However, for some jobs (such as outside work, confined space entry, jobs done only once in a while, or jobs done while workplace controls are being installed), personal protective equipment may be appropriate.

OSHA 1910.132 requires employers to determine the appropriate personal protective equipment for each hazard and to train employees on how and when to use protective equipment.

The following recommendations are only guidelines and may not apply to every situation.

Clothing

- * Avoid skin contact with tert-Butyl Chromate. Wear protective gloves and clothing. Safety equipment suppliers/ manufacturers can provide recommendations on the most protective glove/clothing material for your operation.
- * All protective clothing (suits, gloves, footwear, headgear) should be clean, available each day and put on before work.

Eve Protection

- * Wear indirect-vent, impact and splash resistant goggles when working with liquids.
- * Wear a face shield along with goggles when working with corrosive, highly irritating or toxic substances.
- * Contact lenses should not be worn when working with this substance.

Respiratory Protection

IMPROPER USE OF RESPIRATORS IS DANGEROUS. Such equipment should only be used if the employer has a written program that takes into account workplace conditions, requirements for worker training, respirator fit testing and medical exams, as described in OSHA 1910.134.

- Where the potential exists for exposure over 0.001 mg/m³ (as hexavalent Chromium), use a MSHA/NIOSH approved supplied-air respirator with a full facepiece operated in a pressure-demand or other positive-pressure mode. For increased protection use in combination with an auxiliary self-contained breathing apparatus operated in a pressure-demand or other positive-pressure mode.
 Exposure to 15 mg/m³ (as hexavalent Chromium) is
- * Exposure to 15 mg/m³ (as hexavalent Chromium) is immediately dangerous to life and health. If the possibility of exposure above 15 mg/m³ (as hexavalent Chromium) exists, use a MSHA/NIOSH approved self-contained breathing apparatus with a full facepiece operated in continuous flow or other positive pressure mode.

HANDLING AND STORAGE

- * Prior to working with **tert-Butyl Chromate** you should be trained on its proper handling and storage.
- * tert-Butyl Chromate must be stored to avoid contact with MOISTURE; STRONG BASES (such as SODIUM HYDROXIDE and POTASSIUM HYDROXIDE); STRONG ACIDS (such as HYDROCHLORIC, SULFURIC and NITRIC); ALCOHOLS; HYDRAZINE; and COMBUSTIBLE, ORGANIC or other easily OXIDIZED MATERIALS (such as PAPER, WOOD, SULFUR, ALUMINUM and PLASTICS) since violent reactions occur.
- * Sources of ignition, such as smoking and open flames, are prohibited where **tert-Butyl Chromate** is handled, used, or stored.
- * Metal containers involving the transfer of **tert-Butyl Chromate** should be grounded and bonded.
- * Use only non-sparking tools and equipment, especially when opening and closing containers of **tert-Butyl Chromate**.

QUESTIONS AND ANSWERS

- Q: If I have acute health effects, will I later get chronic health effects?
- A: Not always. Most chronic (long-term) effects result from repeated exposures to a chemical.

- Q: Can I get long-term effects without ever having short-term effects?
- A: Yes, because long-term effects can occur from repeated exposures to a chemical at levels not high enough to make you immediately sick.
- Q: What are my chances of getting sick when I have been exposed to chemicals?
- A: The likelihood of becoming sick from chemicals is increased as the amount of exposure increases. This is determined by the length of time and the amount of material to which someone is exposed.
- Q: When are higher exposures more likely?
- A: Conditions which increase risk of exposure include <a href="https://physical.google.com/physical.google.com/physical.google.com/physical.google.com/physical.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.google.goo
- Q: Is the risk of getting sick higher for workers than for community residents?
- A: Yes. Exposures in the community, except possibly in cases of fires or spills, are usually much lower than those found in the workplace. However, people in the community may be exposed to contaminated water as well as to chemicals in the air over long periods. This may be a problem for children or people who are already ill.
- Q: Don't all chemicals cause cancer?
- A: No. Most chemicals tested by scientists are not cancercausing.

TTI C 11 ' ' C ' ' ' ' 1 1 1 C

The following information is available from:

New Jersey Department of Health and Senior Services Occupational Disease and Injury Services PO Box 360 Trenton, NJ 08625-0360 (609) 984-1863 (609) 292-5677 (fax)

Web address: http://www.state.nj.us/health/eoh/odisweb/

Industrial Hygiene Information

Industrial hygienists are available to answer your questions regarding the control of chemical exposures using exhaust ventilation, special work practices, good housekeeping, good hygiene practices, and personal protective equipment including respirators. In addition, they can help to interpret the results of industrial hygiene survey data.

Medical Evaluation

If you think you are becoming sick because of exposure to chemicals at your workplace, you may call personnel at the Department of Health and Senior Services, Occupational Disease and Injury Services, who can help you find the information you need.

Public Presentations

Presentations and educational programs on occupational health or the Right to Know Act can be organized for labor unions, trade associations and other groups.

Right to Know Information Resources

The Right to Know Infoline (609) 984-2202 can answer questions about the identity and potential health effects of chemicals, list of educational materials in occupational health, references used to prepare the Fact Sheets, preparation of the Right to Know survey, education and training programs, labeling requirements, and general information regarding the Right to Know Act. Violations of the law should be reported to (609) 984-2202.

DEFINITIONS

ACGIH is the American Conference of Governmental Industrial Hygienists. It recommends upper limits (called TLVs) for exposure to workplace chemicals.

A carcinogen is a substance that causes cancer.

The **CAS number** is assigned by the Chemical Abstracts Service to identify a specific chemical.

A combustible substance is a solid, liquid or gas that will burn.

A **corrosive** substance is a gas, liquid or solid that causes irreversible damage to human tissue or containers.

DEP is the New Jersey Department of Environmental Protection.

DOT is the Department of Transportation, the federal agency that regulates the transportation of chemicals.

EPA is the Environmental Protection Agency, the federal agency responsible for regulating environmental hazards.

A **fetus** is an unborn human or animal.

A **flammable** substance is a solid, liquid, vapor or gas that will ignite easily and burn rapidly.

The **flash point** is the temperature at which a liquid or solid gives off vapor that can form a flammable mixture with air.

HHAG is the Human Health Assessment Group of the federal EPA.

IARC is the International Agency for Research on Cancer, a scientific group that classifies chemicals according to their cancer-causing potential.

A **miscible** substance is a liquid or gas that will evenly dissolve in another.

mg/m³ means milligrams of a chemical in a cubic meter of air. It is a measure of concentration (weight/volume).

MSHA is the Mine Safety and Health Administration, the federal agency that regulates mining. It also evaluates and approves respirators.

A **mutagen** is a substance that causes mutations. A **mutation** is a change in the genetic material in a body cell. Mutations can lead to birth defects, miscarriages, or cancer.

NAERG is the North American Emergency Response Guidebook. It was jointly developed by Transport Canada, the United States Department of Transportation and the Secretariat of Communications and Transportation of Mexico. It is a guide for first responders to quickly identify the specific or generic hazards of material involved in a transportation incident, and to protect themselves and the general public during the initial response phase of the incident.

NCI is the National Cancer Institute, a federal agency that determines the cancer-causing potential of chemicals.

NFPA is the National Fire Protection Association. It classifies substances according to their fire and explosion hazard.

NIOSH is the National Institute for Occupational Safety and Health. It tests equipment, evaluates and approves respirators, conducts studies of workplace hazards, and proposes standards to OSHA.

NTP is the National Toxicology Program which tests chemicals and reviews evidence for cancer.

OSHA is the Occupational Safety and Health Administration, which adopts and enforces health and safety standards.

PEOSHA is the Public Employees Occupational Safety and Health Act, a state law which sets PELs for New Jersey public employees.

ppm means parts of a substance per million parts of air. It is a measure of concentration by volume in air.

A **reactive** substance is a solid, liquid or gas that releases energy under certain conditions.

A **teratogen** is a substance that causes birth defects by damaging the fetus.

TLV is the Threshold Limit Value, the workplace exposure limit recommended by ACGIH.

The **vapor pressure** is a measure of how readily a liquid or a solid mixes with air at its surface. A higher vapor pressure indicates a higher concentration of the substance in air and therefore increases the likelihood of breathing it in.

>>>>>> E M E R G E N C Y I N F O R M A T I O N <<<<<<<<

Common Name: tert-BUTYL CHROMATE

DOT Number: None
NAERG Code: No Citation
CAS Number: 1189-85-1

Hazard rating	NJDHSS	NFPA
FLAMMABILITY	Not Found	Not Rated
REACTIVITY	Not Found	Not Rated
EL VIATABLE		

FLAMMABLE

POISONOUS GASES ARE PRODUCED IN FIRE

Hazard Rating Key: 0=minimal; 1=slight; 2=moderate; 3=serious; 4=severe

FIRE HAZARDS

- * tert-Butyl Chromate is a FLAMMABLE MIXTURE.
- * Use dry chemical, sand, water spray or foam to extinguish fire
- * POISONOUS GASES ARE PRODUCED IN FIRE.
- * If employees are expected to fight fires, they must be trained and equipped as stated in OSHA 1910.156.

SPILLS AND EMERGENCIES

If **tert-Butyl Chromate** is spilled or leaked, take the following steps:

- * Evacuate persons not wearing protective equipment from area of spill or leak until clean-up is complete.
- * Remove all ignition sources.
- * Ventilate area of spill or leak.
- * Absorb liquids in vermiculite, dry sand, earth, or a similar material and deposit in sealed containers.
- * Keep **tert-Butyl Chromate** out of a confined space, such as a sewer, because of the possibility of an explosion, unless the sewer is designed to prevent the build-up of explosive concentrations.
- * It may be necessary to contain and dispose of **tert-Butyl Chromate** as a HAZARDOUS WASTE. Contact your
 Department of Environmental Protection (DEP) or your
 regional office of the federal Environmental Protection
 Agency (EPA) for specific recommendations.
- * If employees are required to clean-up spills, they must be properly trained and equipped. OSHA 1910.120(q) may be applicable.

FOR LARGE SPILLS AND FIRES immediately call your fire department. You can request emergency information from the following:

CHEMTREC: (800) 424-9300 NJDEP HOTLINE: (609) 292-7172

HANDLING AND STORAGE (See page 3)

FIRST AID

In NJ, POISON INFORMATION 1-800-764-7661

Eye Contact

* Immediately flush with large amounts of water. Continue without stopping for at least 30 minutes, occasionally lifting upper and lower lids. Seek medical attention immediately.

Skin Contact

* Quickly remove contaminated clothing. Immediately wash contaminated skin with large amounts of water.

Breathing

- * Remove the person from exposure.
- * Begin rescue breathing (using universal precautions) if breathing has stopped and CPR if heart action has stopped.
- * Transfer promptly to a medical facility.

PHYSICAL DATA

Water Solubility: Miscible

OTHER COMMONLY USED NAMES

Chemical Name:

Chromic Acid, Bis(1,1-Dimethylethyl)- Ester

Other Names:

t-Butyl Chromate; di-tert-Butyl Ester of Chromic Acid; Bis (tert-butyl) Chromate

Not intended to be copied and sold for commercial purposes.

NEW JERSEY DEPARTMENT OF HEALTH AND SENIOR SERVICES

Right to Know Program

PO Box 368, Trenton, NJ 08625-0368 (609) 984-2202
